

SPARSH VP330E – The Touch Screen IP Phone

Desk Phone is the backbone of communication for controlling business operations. Today's efficient managers require desk phone with elegant design, smart functionalities and multi-tasking ability as their command center. Matrix presents SPARSH VP330E – The Touch Screen IP Phone, offering perfect blend of Style and Substance for desktop telephony experience.

SPARSH VP330E is an intuitive Touch Screen IP phone integrating the traditional desk phone and 4.3 inch vivid color display in a single device. With On-Screen BLF Keys, Presence and Power over Ethernet (PoE), SPARSH VP330E offers productivity features for speed of operations and collaboration. Thus, making it an ideal choice for reliable and flawless communication.

AT-A-GLANCE:



4.3" Large Color Touch Screen Display



Ergonomic and Modern Design



- 18 Contacts



Superior Voice Quality with High Definition Audio

On-screen BLF monitoring



Presence Indication

Local Phonebook (500 Entries) and LDAP Client



Power over Ethernet (IEEE 802.3af)

Built-in 12 DSS Keys for Feature, Line, Extension



TECHNICAL SPECIFICATIONS

Audio Feature

- Full-duplex Hands-free
 Speakerphone with AEC
- Codecs: G.711(A/ μ), G.722,
- G.723, G.729,
- AEC, AJB, AGC

Phone Features

- Call Hold
- Mute
- Do Not Disturb
- Speed Dial
- Hotline
- Redial
- Call Back
- Auto Answer
- Call Forward
- Call Waiting
- Call Transfer
- Room Monitoring
- Conference
- Directory
- Call Logs
- Paging
- Dial-by-Name
- BLF Softkeys
- Presence

Call Management

- Message Wait Lamp
- Ringer Lamp
- Voice Mail
- Call Pickup Group and Selective
- Paging

Display

- 480x272 pixel Touch-Screen Colour LCD
- LED for Incoming/Ongoing Call, Mute, Hold
- Intuitive User Interface with Icons and Soft keys
- Multiple Languages
- Caller ID with Name, Number

Networking and Security

- SIP v2 (RFC3261)
- IP Assignment: Static/DHCP/PPPoE
- QoS: 802.1p/Q Tagging (VLAN),
- Layer 3 ToS, DSCP
- SRTP for Voice
- Transport Layer Security (TLS)
- AES Encryption for Configuration File
- Digest Authentication using Md5

Physical Features

- 2 x 10/100 Mbps LAN & PC Ports
- 33 keys
- 1 x RJ9 Handset Port
- 1 USB Port
- Dimension (W x D x H): 207 x 335 x 78

Power Supply

- Power Adapter: 5VDC/600mA (Included in the Box)
- Power over Ethernet (IEEE 802.3af)
- Power Consumption: 5W (Typical)
- Connector: DC Power Jack

Mechanical

- Weight: 0.840 Kgs
- Installation: Wall Mount, Table-top
- Color: Black

Environmental

- Operating Temperature Range = 0 to 45°C
- Storage Temperature = 0 to 55°C
- Operating and Storage Humidity = 5 to 95%, RH, Non-Condensing

Certifications

• CE • FCC-15 • RoHS



ABOUT MATRIX





Established in 1991, Matrix is a leader in Telecom and Security solutions for modern businesses and enterprises. An innovative, technology driven and customer focused organization; Matrix is committed to keep pace with the revolutions in the telecom and security industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products like IP-PBX, Universal Gateways, VoIP Gateways and Terminals, GSM Gateways, Access Control, Time-Attendance and Video Surveillance solutions. These solutions are feature-rich, reliable and conform to the international standards. Having global foot-prints in Asia, Europe, North America, South America and Africa through an extensive network of more than 500 channel partners, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many international awards for its innovative products.





MATRIX COMSEC

Head Office

394-GIDC, Makarpura, Vadodara-390 010, India. Ph: +91 265 2630555, Fax: +91 265 2636598 E-mail: Inquiry@MatrixComSec.com SMS 'MATRIX' to +91 99987 55555

www.MatrixTeleSol.com

Due to continuous technology upgradations, product specifications are subject to change without notice.